

1. THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE: Dry pressed ceramic tiles with low water absorption $E_b \leq 0,5\%$; Bla Group, glazed (GL)

2. INTENDED USE OR USES: For walls and floors internal and /or external, including stairs, in buildings and industrial facilities.

3. MANUFACTURER: CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce

4. SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: SYSTEM 4

5. HARMONIZED STANDARD: EN 14411:2012

6. DECLARED PERFORMANCE:

ESSENTIAL CHARACTERISTICS	PERFORMANCE (LEVEL AND/OR CLASS)
Reaction-to-fire performance	A1 / A1 _{FL} <i>Classified Without Testing (CWT)</i>
Release of dangerous substances:	
- Cadmium	$\leq 0,07\text{mg}/\text{dm}^2$
- Lead	$\leq 0,8\text{mg}/\text{dm}^2$
- Other	NPD
Breaking strength:	
- thickness $\geq 7,5\text{mm}$	$\geq 1300\text{ N}$
Bond strength/adhesion [N/mm²]:	
- cementitious adhesives	$\geq 0,5\text{ N}/\text{mm}^2$
- dispersion adhesives	$\geq 1\text{ N}/\text{mm}^2$
- reaction resin adhesives	$\geq 2\text{ N}/\text{mm}^2$
- mortar	NPD
Slippage according to EN 16165:2021, annex B-α_{shod} [°]	$\alpha_{shod} \leq 35^\circ$
Thermal shock resistance	Pass
Durability for:	
- internal use:	Pass
- external use: resistance to freeze-thaw cycles	Pass
Tactility	NPD

A copy of the Declaration of Performance is available on the website: www.cersanit.com; www.opoczno.eu

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:
Kielce, 01.12.2022

Signed on behalf of the manufacturer

QUALITY DIRECTOR
CERSANIT S.A.

Jolanta Grzebna

NPD - No Performance Determined