

1. **THE UNIQUE IDENTIFICATION CODE OF THE PRODUCT TYPE:** Dry pressed ceramic tiles with low water absorption  $E_b \leq 0,5\%$ ; Annex G, Bla Group, unglazed (UGL); polished
2. **INTENDED USE OR USES:** For walls and floors internal and for walls external, in buildings and industrial facilities.
3. **MANUFACTURER:** CERSANIT S.A.; AL. Solidarności 36; 25-323 Kielce
4. **SYSTEM(S) OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE:** SYSTEM 4
5. **HARMONIZED STANDARD:** EN 14411:2012
6. **DECLARED PERFORMANCE:**

**ESSENTIAL CHARACTERISTICS**

**PERFORMANCE (LEVEL AND/OR CLASS)**

<b>Reaction-to-fire performance</b>	A1 / A1 <sub>FL</sub> Classified Without Testing (CWT)
<b>Release of dangerous substances:</b>	
- Cadmium	$\leq 0,07 \text{ mg/dm}^2$
- Lead	$\leq 0,8 \text{ mg/dm}^2$
- Other	NPD
<b>Breaking strength:</b>	
- thickness $\geq 7,5 \text{ mm}$	$\geq 1300 \text{ N}$
<b>Bond strength/adhesion [N/mm<sup>2</sup>]:</b>	
- cementitious adhesives	$\geq 0,5 \text{ N/mm}^2$
- dispersion adhesives	$\geq 1 \text{ N/mm}^2$
- reaction resin adhesives	$\geq 2 \text{ N/mm}^2$
- mortar	NPD
<b>Slippage according to EN 16165:2021, annex B-<math>\alpha_{shod}</math> [°]</b>	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability for:</b>	
- internal use:	Pass
- external use: resistance to freeze-thaw cycles	Pass
<b>Tactility</b>	NPD

A copy of the Declaration of Performance is available on the website: [www.cersanit.com](http://www.cersanit.com); [www.opoczno.eu](http://www.opoczno.eu)

The performance of the above product is in accordance with the Declaration of Performance. This declaration of performance shall be issued in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer referred to above.

Place, date:  
Kielce, 01.12.2022

Signed on behalf of the manufacturer

QUALITY DIRECTOR  
CERSANIT S.A.  
  
Jolanta Grzebna

NPD - No Performance Determined